

FLUID COOLING | Shell & Tube SSC Series



Features

- Preferred for New Oil-Water Applications
- Rugged Steel Construction
- Low Cost
- Type 316 Stainless Steel Construction
- Custom Designs Available
- Competitively Priced



- NPT, SAE O-Ring, SAE Flange, or BSPP Shell Side Connections Available
- End Bonnets Removable for Servicing
- Mounting Feet Included (May be rotated in 90° increments)

Ratings Standard

Maximum Shell Pressure 300 psi

Maximum Tube Side Pressure 150 psi

Maximum Temperature 300°F

Materials SSC Series

Tubes 316 Stainless Steel

Tubesheets 316 L Stainless Steel

Shell 316 L Stainless Steel

Shell Connections 316 L Stainless Steel

Baffles 316 Stainless Steel

End Bonnets 316 Stainless Steel

Mounting Brackets Mild Steel

Gaskets Nitrile Rubber/Cellulose Fiber

Nameplate Aluminum Foil

How to Order

	-		-		-		-		-		-			
Model Series SSC CS & SSCS CM & SSCM CF CFM CA/SSCA		Model Size Selected		Baffle Spacing		Tube Diameter Code 4 - 1/4" 6 - 3/8"		Tube Side Passes 0 - One Pass T - Two Pass F - Four Pass		Cooling Tube Material SS - Stainless Steel		End Bonnet Material SB - Stainless Steel		Tubesheet Material S - Stainless Steel

C = NPT Shell side connections; NPT Tube side connections

CS = SAE O-Ring Shell side connections; NPT Tube side connections

CM = BSPP Shell side connections; BSPP Tube side connections

CF = SAE Flange (with UNC threads) Shell side connections; NPT Tube side connections

CFM = SAE Flange (with Metric threads) Shell side connections; BSPP Tube side connections

SSC = NPT Shell side connections; NPT Tube side connections


SSCS = SAE O-Ring Shell side connections; NPT Tube side connections

SSCM = BSPP Shell side connections; BSPP Tube side connections

CA/SSCA = 150# ASME RF Flanges on Shell; NPT Tube side connections

Dimensions

One Pass




Flange Size	GG	HH	Z - CF	Z - CFM
1	1.03	2.06	3/8-16 UNC	M-10
1.50	1.41	2.75	1/2-13 UNC	M-12
2	1.69	3.06		
3	2.44	4.19	5/8-11 UNC	M-16

MODEL SIZE	A	B	C	D		E	F	G	H	J	K NPT	L		M	N	P	R NPT	S NPT/ BSPP	T				
				NPT/BSPP SAE O-RING	SAE FLANGE							NPT/BSPP FLANGE	SAE O-RING										
614	3.25	4.50	10.00	2.62	2.88	16.38	2.75	4.18	1.62	.44 DIA.	(3)	1.00	#16 15/16-12 UNF-2B	17.18	3.59	.40	(2)	1.50	.38				
624			20.00			26.38							27.18										
814	4.25	6.00	9.00	3.25	3.50	16.62	3.50	4.25	1.75			1.50	#24 17/8-12 UN-2B	17.88	4.44	.63		2.00	—				
824			19.00			26.62								27.88									
836			31.00			38.62								39.88									
1014	5.25	6.75	9.00	3.75	4.00	17.12	4.00	5.25	2.00	.50 x .75	(3)			2.00	#32 2 1/2-12 UN-2B	19.09	5.05			.92	(4)	3.00	—
1024			19.00			27.12										29.09							
1036			31.00			39.12						41.09											
1224	6.25	7.75	18.25	4.25	4.88	27.13	4.50	6.25	2.50			2.00	#32 2 1/2-12 UN-2B	30.00	5.87	1.43	(4)	4.00	—				
1236			30.25			39.13								42.00									
1248			42.25			51.13				54.00													
1260			54.25			63.13				66.00													
1724	8.62	10.50	17.00	5.84	6.81	27.50	5.75	8.25	3.50	.62 x .88	(3)			3.00	—	31.47				7.23	1.99	(4)	4.00
1736			29.00			39.50						43.47											
1748			41.00			51.50						55.47											
1760			53.00			63.50						67.47											
1772			65.00			75.50						79.47											

NOTE: We reserve the right to make reasonable design changes without notice. Consult factory. All dimensions are inches.

Performance Curves



*Shipping Weights are approximate